HENRY HNKM70

Henry One Hole Gooseneck Integrated Pull Spray Kitchen Faucet with Lever Handle



TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Adjustable Spray

Deck Thickness Maximum: 3 1/4" Deck Thickness Minimum: 1/4"

Depth/Width: 11 3/4"

Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 2.0, 1.75, 1.5

How Restriction Options: 2.0, 1.75, 1.5 Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 49"

Height: 17"

Inlet Connection Size: 3/8"

Inlet Connection Type: Compression Connector Hoses

Length: 11 3/4"

Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm

Spout Swivel: Y

Spray Included In Unit: Y

Suggested Application: Bar, Kitchen, Laundry

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 30.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN HENRY ONE HOLE GOOSENECK INTEGRATED PULL SPRAY KITCHEN FAUCET WITH LEVER HANDLE | HNKM70

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

HNKM70X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

The stately single hole fitting stands on a tall well formed pillar with a tapered lever handle. Practical as well a beautiful, this fitting has a hand spray for washing vegetables, rinsing the sink or cleaning pots

Spray features a trigger to switch between aerated stream and jet spray

Spray is held in place with a counter weighted magnet

Handle rotates toward the front to prevent contact with backsplash

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in other flow options. Contact a sales associate for details

CERTIFICATIONS



PRODUCT (NOTES)

HENRY HNKM70

Henry One Hole Gooseneck Integrated Pull Spray Kitchen Faucet with Lever Handle

